



401 Congress Ave Suite 1540 Austin, Tx 78701 Ph.512.687.3433 Fax 512.519.9191
 Web: <http://www.southcoastauto.us> Email: darby@southcoastauto.us

Model 2028-SX2, 2028-SX4

General Specifications	
Motor Power (hp)	5.5 (standard)
Battery Voltage (v)	48
Battery Quantity (pcs)	6 - 8v 48v Trojan T875 (optional)
Solar Panel	180 watt, 60v, 3 amps per hour
Range with Solar (miles)	55+
Max. Speed (m/h)	22
Climbing Ability (loaded)	28° incline
Overall Dimensions (ft)	7.70 L x 3.87 W x 5.83 H
Max. Loading Weight (lbs)	755 lbs
Net Weight (lbs)	1100 lbs
Warranty	1 year parts
Configuration:	
Windshield	Split Windshield (optional)
Upholstery	Dualife Seamless Vinyl
Controller	Curtis Programmable - Model 1244-5451 <i>compatible with model 1307 programmer</i>
Brake System	Self Adjusting Drum Brakes
Suspension	Leaf Springs and Shocks
Rear Axle	19 Spline
Steering	Rack and Pinion
Wheels	8" Tires (standard), 10" Tires (optional)
Charger	48v Automatic Charger



Model 2041-SX4 4-Seat Back to Back:	
Specifications	Same as 2024-SX2
Dimensions	Add 14" to length and 30 lbs

Model 2020ASZ-X4 All Terrain

General Specifications:	
Passenger Capacity	4
Voltage (V)	48V
Range (loaded)	46.6 miles
Max. Speed (m/h)	19.88
Max. Climbing Ability (loaded)	28%
Overall Dimensions (L x W x H) (ft)	8.20 x 3.94 x 6.23
Max. Loading Weight (lbs)	838 lbs
Net Weight (lbs)	1058 lbs
Container Quantity:	
If carts are ordered WITH the top basket, front basket and bumper	
Qty/40'	12 pcs
Qty/40'HQ	18 pcs
If carts are ordered WITHOUT the top basket, front basket and bumper	
Qty/40'	14 pcs
Qty/40'HQ	20 pcs



Configurations: ("S" for Standard and "O" for Optional Configuration)		
Body	Steel Framework & Injected Plastics	S
Body Color (front and rear body)	Camouflage	S
	Solid Color	O
Roof	Fiberglass	S
Roof Color	Solid Color	S
Windshield	One-Piece See-Through	S
	Foldable	O
Seats:	1) Backrest and Cushion	S
	2) Armrest	S
	3) Rear Foldable Seat	S
Floor Protective Side	Non-Slipping Plastic	S
	Stainless Steel	S
Front bumper	Steel	O
Front basket		O
Top basket		O
Lighting system and horn	Front headlights, taillights(combined brake lights with reverse lights), with DC-DC converter (converting from 48V to 12V) and horn	S

Dashboard	Injected plastic 1 battery charging meter, combined switch, key ignition, forward/reverse switch, horn switch	S S
Battery	trojan battery t605 X 8pcs	S
Motor (hp)	5.5	S
Controller	Curtis brand 1268	S
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake System	mechanical brake + parking brake system	S
Accelerator	Stepless speed change	S
Suspension System	Integrative front axle, leaf spring+vibration absorber	S
Driving Mode	Rear axle two stage deceleration, motor direct driving	S
Rear axle	Integrative rear axle, leaf spring + vibration absorber	S
Wheel and tire	25 x 10-12 tire, 12*7 Steel wheel 22 x 10-10 tire, 10*8 Steel wheel	S O
Seat belt	2-point	O
Hand Bar		S
Rear view mirror	external	S

Model 6042-SX4

General Specifications:	
Passenger Capacity	4
Motor Power (hp)	5.5- 6.85
Battery Voltage (v)	48
Battery Quantity (pcs)	8 - 6v T605 Trojan (optional)
Range (loaded) (miles)	49
Max. Speed (m/h)	24.85 m/h (normally set at 20.51 m/h if no request for 24.85 m/h)
Minimum Turning Radius (ft)	13.12
Max. Climbing Ability (loaded)	20%
Max. Movement After Brake	13.12 feet
Overall Dimensions (ft)	9.65 L x 4.6 W x 5.68 H
Max. Loading Weight (lbs)	1499.14 lbs



Configurations: ("S" for Standard and "O" for Optional Configuration)		
Body	Steel Framework + Fiberglass Body	S
Solar Roof	Aluminum Frame + Fiberglass with Solar Panel, 120 watts @ 60 volts to charge a 48 volt battery system (eight -6 volt batteries) = 2.0 amp charge per hour in direct sunlight (10 amps per day winter or 16 amps per day summer)	S
Windshield	Tempered glass	S
Seats:		
1) Backrest and Cushion	Sponge + Artificial Leather	S
2) Armrest	Soft Expanded Plastic	S
Seat Belt	4 pcs per cart	O
Hand Holder for Front Passenger	1 pc hand holder under the roof	S
Hand Holder for Rear Passenger	2 pcs fixed under the roof	O
Storage Net	1 pc each backrest	S
inner Rear View Mirror	1 pc	S
Side Rear View Mirror	2 pcs per cart	O
Floor	Bamboo + Artificial Leather	S
Dashboard	Forward/reverse switch, headlight indicator, turn signalS/O indicator, ignition key, voltmeter, ammeter, emergency switch, turn signal switch, headlight switch, windscreen wiper switch, horn button, radio and CD player (extra); storage for miscellaneous items (extra) if with Speedometer	O
Speaker for Radio and Tape Player	2 pcs	O
Lighting System	2 headlights, 2 front turn signals, 2 rear turn signals and 2 rear brake lights	S
Horn and Reverse Alarm		S
Battery	Trojan Battery T605	O
Motor	Sepex Motor, 5.5 hp ADC Sepex Motor, 6.85hp	S O
Controller	Sevcon from UK Curtis controller	O S
Steering	Rack and Pinion	S
Brake System	Rear and front drum pneumatic brake system	S
Accelerator	Stepless speed change	S
Front End and Front Suspension	Independent Suspension	S
Rear End	With primary speed reducer and speed-change gear box	S
Driving Mode	Rear Wheel Drive	S
Tire	10" Wheel and Tire	S
Charger	48v Automatic Charger	S

Model 6060J-X2

General Specifications:	
Passenger Capacity	2
Range (loaded)	49 miles
Max. Speed (m/h)	18.64
Minimum turning radius (ft)	9.51 ft
Max. Climbing Ability (loaded)	20%
max. loading capacity (lbs)	661.39 lbs
max. lifting height (m)	19.69 ft
Overall Dimensions (LxWxH) (m)	11.40 x 4.56 x 7.05
Truck motor (hp)	4.02
Lifter motor (hp)	1.98
Battery quantity (pcs)	8
Voltage of each battery (V)	6
battery capacity (AH)	180
Qty/40'	3



Notes: all above offers are based on full container order quantity. 2% free parts will be provided with each shipment.

Configurations: ("S" for Standard and "O" for Optional Configuration)		
Body	Steel Framework & Steel Plate Body	S
Seats:		
1) Backrest and Cushion	Sponge + Artificial Leather	S
2) Armrest	Stell Pipe	S
Floor	Bamboo Board & Plastic	S
Side Rear View Mirror	One piece each side	O
Cover for Rear Bed	Plywood	S
Battery	Trojan Battery T605, 8 pcs	O
Motor (hp)	4.02	S
Controller	Curtis Brand	S
Lights	Front: 2 Headlights, 2 front turn signals; Back: 2 rear turn signals, 2 brake lights	S
Dashboard	Voltmeter, Ammeter, Speedometer, turn signal indicator, headlight indicator, emergency switch, ignition key; Headlight switch, turn signal switch, horn button	S
DC/DC Converter	48V/12V DC/DC	S
Horn and reverse alarm		S
Cup drinker holder	1 ps	S
Steering system	Rack and Pinion Steering System	S

Brake System	Front and Rear Drum Pneumatic Brake System	S
Front End and Suspension System	independent suspension, cylinder pneumatic vibration absorber	S
Rear End and Suspension System	integrated rear end, steel plate spring suspension, cylinder pneumatic vibration absorber	S
Transmission System	Clutch, 4F+1R gear box, transmission shaft	S
Tire	145/80-R12	S
Seat Belt	2 point seat belt	O
Front Canvas Roof with Windshield		O
Hub Cover		S
Accessories		
Charger	China Origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S